

USB-TRx

simplifying program transfer to CNC



FEATURES

- TRANSMIT / RECEIVE
 - On single button press
 - Programs from / to USB Memory Stick
 - Through RS-232 Port
 - No need for PC connection
- USER INTUITIVE WORKFLOW
 - Relevant instructions on the display
 - Easy and quick program browsing
 - Configurable settings
- MACHINES SUPPORTED
 - Fanuc
 - Haas
 - Siemens
 - Mitsubishi
 - & Others

TECHNICAL SPECIFICATION

POWER

DC +12V, 500mA
ON/OFF through power button

USB PORT

USB memory stick
Upto 32GB
Standard-A USB plug type
FAT32 File System

RS232 PORT

Full Duplex
9 Pin D-type Male
2400 ~ 115200 baud
Hardware / None Flow Control
Even / Odd / None Parity
1 / 2 Stop bits
7 / 8 Data bits

CABLE

1m Length
9pin Female to 25 pin Male

DISPLAY

16 x 2 Alphanumeric Character

KEYPAD

Up / Down Keys
Transmit and Receive Keys

LEDs

Transmit indication
Receive indication
Battery status indication

BATTERY

9-volt battery support

SIZE

180 x 100 x 50 MM (L x B x T)

WEIGHT

380 grm

NAT SYSTEMS
We Automate